PAGE 3/14 \* RCVD AT 9/8/2004 12:02:45 PM [Eastern Daylight Time] \* 5/4:05/16 \* DNIS-8729306 \* CSID:9106/21839 \* DURATION (mm-ss):04-08

U.S. PTO APPLICATION/CONTROL NUMBER: 10/775,970	art unit: unassigned
Claims	

What is claimed is:

1. A fiber optic system comprising:

fiber optic glass panels;

a color frequency interface that allows an individual to select a specific color frequency and the color source would project the intensity of the light signal to determine the color(s) displayed [on] <u>inside</u> the fiber optic glass panel(s) of an automobile, boat, building structure, or the like; and

an image frequency interface that allows an individual to select a specific image frequency and the image source would communicate the intensity of the light signal to determine the image(s) displayed [on] <u>inside</u> the fiber optic glass panel(s) of an automobile, computer, television, boat, aircraft, camouflaging and/or cloaking device, or the like.

- 2. The system of claim 1, wherein the color/image frequencies interface is connecting a light source.
- 3. The system of claim 2, wherein the light source is connecting a color and/or image source.
- 4. The system of claim 3, wherein the color and/or image source is connecting fiber optic strands.

PAGE 4/14 \* RCVD AT 9/8/2004 12:02:45 PM [Eastern Daylight Time] \* SVR:USPTO-EFXRF-1/0 \* DNIS:8729306 \* CSID:9106721839 \* DURATION (mm-55):04-08

U.S. PTO APPLICATION/CONTROL NUMBER: 10/775,970

ART UNIT: UNASSIGNED

5. The system of claim 4, wherein the fiber optic strand(s) are connecting [the fiber optic glass panels width of internal refraction and/or glass] an optical lens for expanding the colors or images inside the fiber optic glass panels.

6. A method of producing fiber optic light signals comprising:

fiber optic glass panels;

a color frequency interface that allows an individual to select a specific color frequency and the color source would project the intensity of the light signal to determine the color(s) displayed [on] <u>inside</u> the fiber optic glass panel(s) of an automobile, boat, building structure, or the like; and

an image frequency interface that allows an individual to select a specific image frequency and the image source would communicate the intensity of the light signal to determine the image(s) displayed [on] <u>inside</u> the fiber optic glass panel(s) of an automobile, computer, television, boat, aircraft, camouflaging and/or cloaking device, or the like.

- 7. The method of claim 6, wherein the color/image frequencies interface is connecting a light source.
- 8. The method of claim 7, wherein the light source is connecting a color and/or image source.
- 9. The method of claim 8, wherein the color and/or image source is connecting fiber optic strands.
- 10. The method of claim 9, wherein the fiber optic strand(s) are connecting [the fiber optic glass panels width of internal refraction and/or glass] an optical lens for expanding the colors or images inside the fiber optic glass panels.

11. A method of producing fiber optic colors and images comprising:

fiber optic glass panels;

a color frequency interface that allows an individual to select a specific color frequency and the color source would project the intensity of the light signal to determine the color(s) displayed [on] inside the fiber optic glass panel(s) of a computer or television display devices, or the like; and

an image frequency interface that allows an individual to select a specific image frequency and the image source would communicate the intensity of the light signal to determine the image(s) displayed [on] inside the fiber optic glass panel(s) of an automobile, computer, television, boat, aircraft, camouflaging and/or cloaking device, or the like.

- 12. The method of claim 11, wherein the color/image frequencies interface is connecting a light source.
- 13. The method of claim 12, wherein the light source is connecting a color and/or image source.
- 14. The method of claim 13, wherein the color and/or image source is connecting fiber optic strands.
- 15. The method of claim 14, wherein the fiber optic strand(s) are connecting [the fiber optic glass panels width of internal refraction and/or glass] an optical lens for expanding the colors or images inside the fiber optic glass panels.
- 16. A system of displaying television and computer signals comprising:

PAGE 6/14 \* RCVD AT 9/8/2004 12:02:45 PM [Eastern Daylight Time] \* 5VR:USPTO-EFXRF-1/0 \* DN/6:8729306 \* CSID:9106721839 \* DURATION (mm-ss):04-08

U.S. PTO APPLICATION/CONTROL NUMBER: 10/775,970

ART UNIT: UNASSIGNED

fiber optic glass panels;

a color frequency interface that allows an individual to select a specific color frequency and the color source would project the intensity of the light signal to determine the color(s) displayed [on] inside the fiber optic glass panel(s) of an automobile, boat, building structure, or the like; and

an image frequency interface that allows an individual to select a specific image frequency and the image source would communicate the intensity of the light signal to determine the image(s) displayed [on] inside the fiber optic glass panel(s) of an automobile, computer, television, boat, aircraft, camouflaging and/or cloaking device, or the like.

- 17. The system of claim 16, wherein the color/image frequencies interface is connecting a light source.
- 18. The system of claim 17, wherein the light source is connecting a color and/or image source.
- 19. The system of claim 18, wherein the color and/or image source is connecting fiber optic strands.
- 20. The system of claim 19, wherein the fiber optic strand(s) are connecting [the fiber optic glass panels width of internal refraction and/or glass] an optical lens for expanding the colors or images within inside the fiber optic glass panels.